



...with an abrasion resistant, low friction cover.

RWS-L is a lightweight, **Low Force to Bend** hose. The exterior polymer blend with corrugations that are wide and smooth ensures low friction and ease of movement. This suction and discharge hose is designed for extra flexibility. **Wear resistance** is achieved by its "ARC" abrasion resistant cover. **RWS-L** delivers taste and odor free flow with easy clean up.(Meets 3-A* standards, USDA requirements and FDA compliant).

_								
-	e	2	•		r	Δ	c	۰
	┖	а		u	•	_	3	•

- Low Friction/Easy Drag
- Extreme Flexibility Low Force to Bend
- Easily Placed or Repositioned
- Abrasion Resistant Cover
- Full Temperature Range
- Will Not Impart Taste or Odor
- CIP Suitable
- Exterior corrugations allow for draining
- Long Length 130 ft.

Applications:

- Food, Beverage and Dairy
- Craft Brewing, Wine and Spirits
- Tank Hauler/Transport
- Larger Diameter Filling Equipment
- Durable Alternative to PVC
- High Alcohol Suction & Discharge

MODEL	I.D.	0.D.	WORKING PRESSURE	MIN. BEND Radius		VAC. IN HG.	LENGTH
RWS-L150	11/2"	1.93"	115 PSI	3.0"	.65 lbs.	27"	130'
RWS-L200	2"	2.44"	115 PSI	4.0"	.85 lbs.	27"	130'
RWS-L250	21/2"	2.97"	115 PSI	5.0"	1.15 lbs.	27"	130'
RWS-L300	3"	3.46"	115 PSI	6.0"	1.37 lbs.	27"	130'

TUBE White, FDA, 3-A*, Chlorobutyl **REINFORCEMENT** High strength synthetic cord with steel wire helix **RECOMMENDED CLEANING** CIP. COP

COVER Gray Thermoplastic w/white stripe TEMP. RANGE -40 to 250°F



RWS-L Wine & Spirits - Lite

ALL R-Series hose products meet/comply: USDA Class III requirements, FDA CFR Title 21.1772600, 3-A 18-03 *The 3-A 62-02, standard applies only to assemblies of 3/4" diameter and larger.

WARNING Working pressure ratings for all Flex-Rite[™] brand hoses are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "R" series applications that exceed 200° F contact manufacturer for suggestions.

