

Flex-Rite™



TRS

"EPDM Rubber Covered
Smooth Bore"

...provides extended service life!

TRS has dual steel wires helically wound through the wall which provides crush, kink and vacuum resistance. Wrapped in a durable, chemical resistant, EPDM cover, TRS is ideal where external abrasion resistance is required.

Features:

- Extended Service Life
- Smooth, Flexible Fluoropolymer Liner
- Superb flexibility
- Strong, Kink Resistant
- Chemical Resistant EPDM Cover

Applications:

- Transport
 - Pharmaceuticals
 - Chemicals
 - Food
 - Beverages
 - Receiving Bay
- Cleaning/Sterilizing

MODEL	I.D.	O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT PER FT.	VAC. IN HG.	LENGTH
TRS050	1/2"	.97"	300 PSI	1.5"	.32 lbs.	30"	60'
TRS075	3/4"	1.27"	300 PSI	3.0"	.48 lbs.	30"	60'
TRS100	1"	1.48"	300 PSI	3.5"	.57 lbs.	30"	60'
TRS150	1 1/2"	2.04"	300 PSI	4.5"	.89 lbs.	30"	60'
TRS200	2"	2.54"	300 PSI	7.0"	1.22 lbs.	30"	60'
TRS250	2 1/2"	3.07"	300 PSI	10.0"	1.64 lbs.	30"	60'
TRS300	3"	3.82"	200 PSI	14.0"	2.68 lbs.	30"	60'
TRS400	4"	4.84"	150 PSI	18.0"	3.98 lbs.	30"	60'

TUBE FEP, 3-A*, USP Class VI & FDA Criteria

REINFORCEMENT Steel wire, helically wound

RECOMMENDED CLEANING CIP, SIP - Steam shouldn't exceed 25 psi/250°

COVER Green EPDM w/white stripe

TEMP. RANGE -20 to 300° F

3-A LISTED 3/4" I.D. and over



Shown with conductive tube (special order consult factory)

WARNING Working pressure ratings for all Flex-Rite™ brand hoses are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "T" series applications that exceed 250° F contact manufacturer for suggestions.



513-889-2118 • 855-357-4110 • 513-889-2125 FAX

5452 Spellmire Dr, Cincinnati, OH 45246

www.acesanitary.com

ASTSB22118